DATE	REV	REVISION CHANGES	ECN	APP'D BY
09/19/18	A0	AS DRAWN	-	ADB















A-CODE (4 PIN)



A-CODE (5 PIN)

NOTES:

1. CONNECTOR MATERIALS:
   HOUSING: THERMOPLASTIC UL94 V-0
   CONTACTS/SHIELD: COPPER ALLOY
   O-RING MATERIAL: SILICONE UL94 V-0
   EPOXY POTTING COMPOUND IN REAR CAVITY
   SHIELD PLATING: NICKEL
   CONTACT PLATING: SELECTIVE GOLD (1 uIN) OR EQUIVALENT IN THE CONTACT AREA
2. FOR PRODUCT SPECIFICATIONS SEE PR039-01
3. DIMENSIONS AND TOLERANCES COMPLY WITH IEC 61076-2-101 STANDARD.
4. PLUG ACCOMMODATES CABLE Ø6.00 – 6.50
5. CODING: A-STANDARD
6. TIN PLATED SOLDER CUP CONTACTS ACCOMMODATE 22 AWG WIRE
7. CURRENT RATING: 4 AMPS MAX
8. INSULATION RESISTANCE: 100 MOHMS MIN @ 500 VDC
9. DEGREE OF PROTECTION: IP67
10. TEMPERATURE RANGE: -20°C TO +85°C
11. MATING CYCLES: 100 INSERTIONS

NUMBER OF CONTACTS	PART NUMBER
5	SS-12000-020
4	SS-12000-019

RoHS

THIRD ANGLE PROJECTION

DO NOT SCALE DRAWING
DRAWING IS SUBJECT TO CHANGE WITHOUT NOTICE
DIMENSIONS: METRIC
UNLESS OTHERWISE SPECIFIED TOLERANCES ARE ±0.13 [.005] ANGLES ARE ± 1°
SHEET NO. 1 OF 1

stewart CONNECTOR a bel group
11118 Susquehanna Trail South
Glen Rock, PA 17327-9199
(717) 235-7512
http://www.stewartconnector.com

TITLE: FIELD TERMINATED PLUG WITH SOLDER CUP CONTACTS M12-A CODE, FEMALE

THIS DRAWING AND THE SUBJECT MATTER SHOWN THEREON ARE CONFIDENTIAL AND THE PROPRIETARY PROPERTY OF STEWART CONNECTOR AND SHALL NOT BE REPRODUCED, COPIED, OR USED IN ANY MANNER WITHOUT PRIOR WRITTEN CONSENT OF STEWART CONNECTOR. ONE OR MORE U.S. PATENTS MAY APPLY TO THIS PRODUCT. FOR DETAILS, PLEASE VISIT: HTTP://BELFUSE.COM/STEWART/STEWART_PATENTS/

DRN BY:	BTS	DATE	09/06/18
APPD BY:	ADB	DATE	09/19/18
DWG NO.	CT120010	REV.	A0

AutoCAD A1 Metric